



CHARMAG

Width B of doors (mm)
Support thickness (mm)

Admissible weight of doors (N)

Hitsattavat nostosaranat, oven max. paino newtoneina (N / 10 = kg)

Split hinges type No. 7010.0 - 7011.0 - 7012.0 - 7013.0 - 7014.0 - 7004.00 - 7005.00

For door heights H ≥ 1900mm

Length of split hinges (mm) Saranan pituus (mm)

Leveys mm	Materiaalin vahvuus mm	40	45	50	60	70	80	100	120	135	140	150	160	180	200
600	1	350	350	500	600	700	800	1000	1350	1600	1600	1800	2000	2350	2550
	2	700	700	1000	1200	1400	1600	2000	2700	3200	3200	3600	4000	4700	5100
	3	1050	1050	1500	1800	2100	2400	3000	4050	4800	4800	5400	6000	7050	7650
800	1	300	300	400	500	600	700	850	1150	1300	1350	1500	1650	1950	2100
	2	600	600	800	1000	1200	1400	1700	2300	2600	2700	3000	3300	3900	4200
	3	900	900	1200	1500	1800	2100	2550	3450	3900	4050	4500	4950	5850	6300
1000	1	250	250	350	450	500	600	750	950	1150	1150	1300	1400	1650	1800
	2	500	500	700	900	1000	1200	1500	1900	2300	2300	2600	2800	3300	3600
	3	750	750	1050	1350	1500	1800	2250	2850	3450	3450	3900	4200	4950	5400
1200	1	200	200	300	400	450	500	650	850	1000	1000	1100	1200	1450	1550
	2	400	400	600	800	900	1000	1300	1700	2000	2000	2200	2400	2500	3100
	3	600	600	900	1200	1350	1500	1550	2550	3000	3000	3300	3600	4350	5650
1400	1	200	200	250	350	400	450	550	750	850	900	1000	1100	1250	1400
	2	400	400	500	700	800	900	1100	1500	1700	1800	2000	2200	2500	2800
	3	600	600	750	1050	1200	1350	1650	2250	2550	2700	3000	3300	3750	4200
1500	1	150	150	250	300	350	400	550	700	800	850	950	1000	1200	1300
	2	300	300	500	600	700	800	1100	1400	1600	1700	1800	2000	2400	2600
	3	450	450	750	900	1050	1200	1650	2100	2400	2550	2850	3000	3600	3900